



KEY FEATURES

- Replaces up to 1000 Watts
- Engineered with exceptional thermal management
- Operating temperature from -50°C to 60°C
- Extremely durable
- Water resistant(IP 65)
- Unparalleled quality of light
- Durable construction
- 5 Year Warranty



APPLICATIONS

- Industrial Buildings
- Commerical Buildings
- Automotive Dealerships
- Retail Malls/Plazas
- Construction Sites
- Municipalities
- Public Transit Buildings



| PRODUCT CODE | WATTAGE | LUMENS | AMPERAGE | INPUT VOLTAGE | DIMMING RANGE | CCT   | WEIGHT(KG) | (INCHES)<br>DIMENSIONS<br>(L) X (W) X (H) | DLC NUMBER |
|--------------|---------|--------|----------|---------------|---------------|-------|------------|---|------------|
| EPL56R*      | 62W     | 5,700  | 0.5237A  | 90-240 AC     | 0-100%        | 5700K | 7.6        | 62.5 x 25.3 x 9.1                         | PFCMPUH9   |
| EPL96R*      | 110W    | 8,600  | 0.9315A  | 90-240 AC     | 0-100%        | 5700K | 9.95       | 72.5 x 25.3 x 9.1                         | PPCX996E   |
| EWP112R*     | 114W    | 11,100 | 0.9674A  | 90-240 AC     | 0-100%        | 5700K | 10.6       | 77.8 x 25.3 x 9.1                         | P578WPPY   |
| EPL144R*     | 165W    | 14,000 | 1.386A   | 90-240 AC     | 0-100%        | 5700K | 12.5       | 84.7 x 25.3 x 9.1                         | PTGRV59A   |

(\* ) ALSO AVAILABLE IN 347V

COMMENTS