









Replaces up to 1000 Watts

Engineered with exceptional thermal management

Operating temperature from -50°C to 60°C

Extremely durable

Water resistant(IP-65)

Unparalled quality of light

Durable construction

5 Year Warranty











APPLICATIONS

Industrial Buildings

Commerical Buildings

Automotive Dealerships

Retail Malls/Plazas

Construction Sites

Municipalities

Public Transit Buildings



PRODUCT CODE	WATTAGE	LUMENS	AMPERAGE	input Voltage	DIMMING RANGE	ССТ	WEIGHT(KG)	(INCHES) DIMENSIONS (L) X (W) X (H)	DLC NUMBER
EWPW 56R*	63W	5785	0.52A	90-240 AC	0-100%	5700K	6.5	36.8 x 24 x 18.9	P8MF19GZ
EWPW 96R*	108W	9085	0.915A	90-240 AC	0-100%	5700K	10.5	52.3 x 24 x 18.9	PJHQHHDV
EWP112R*	120W	11485	1.025A	90-240 AC	0-100%	5700K	10.5	52.3 x 24 x 18.9	PTR8SSPT
EWP 144R*	162W	13535	1.379A	90-240 AC	0-100%	5700K	12.5	59 x 24 x 18.9	PW919GNW

(*) Also available in 347V

COMMENTS